

# **BLANK PAGE**



# Indian Standard

# DIMENSIONS FOR GENERAL PURPOSE PUSH-PULL SINGLE-POLE CIRCUIT-BREAKERS FOR AIRCRAFT

UDC 621·316·57:629·13·066



© Copyright 1979

INDIAN STANDARDS INSTITUTION MANAK BHAVAN, 9 BAHADUR SHAH ZAFAR MARG NEW DELHI 110002



IS: 8852 - 1978

## Indian Standard

## DIMENSIONS FOR GENERAL PURPOSE PUSH-PULL SINGLE-POLE CIRCUIT-BREAKERS FOR AIRCRAFT

## Aircraft Electrical Equipment Sectional Committee, ETDC 55

Chairman

Representing

GP CAPT P. GOPALAN

Aeronautical Development Establishment (R&D) (Ministry of Defence), Bangalore

Members

WG CDR G. B. SINGH ( Alternate to

Gp Capt P. Gopalan )

Shri M. N. Arora SHRI M. S. EKBOTE ( Alternate )

SHRI H. V. BADRINATH

SHRI S. BALAKRISHNA SHRI M. K. BASU

WG CDR H. R. SEETHARAM ( Alternate )

GP CAPT H. S. BHATIA

SHRI H. C. PANDE ( Alternate ) SHRI M. DEY

SHRI K. V. R. RAO ( Alternate )

SHRI RAM KUMAR GUPTA SHRI P. MUKUNDAN ( Alternate )

SHRI A. N. GHOSH

SHRI R. NARASIMHAN SHRI A. PURSHOTAM

Indian Airlines Corporation, New Delhi

Wireless Planning and Coordination Wing (Ministry of Communications), New Delhi

National Aeronautical Laboratory, Bangalore Hindustan Aeronautics Ltd, Bangalore

Directorate of Technical Development and Production (Air) (Ministry of Defence), New Delhi

Indian Cable Co Ltd. Calcutta

Delton Cable Industries Pvt Ltd, Delhi

Development Commissioner, Small Scale Industries,

New Delhi

Civil Aviation Department, New Delhi International Airports Authority of

New Delhi

SHRI K. S. JAYRAM ( Alternate ) Dr Vepa Narayana Murthy

Indian Space Research Organization (Vikram Sarabhai Space Centre), Trivandrum

SHRI K. SANKARANARAYANAN Directorate General of Technical Development. New Delhi

(Continued on page 2)

India.

## © Copyright 1979

#### INDIAN STANDARDS INSTITUTION

This publication is protected under the Indian Copyright Act (XIV of 1957) and reproduction in whole or in part by any means except with written permission of the publisher shall be deemed to be an infringement of copyright under the said Act.

#### IS: 8852 - 1978

( Continued from page 1)

Members

Representing

SHRI C. SITAPATI RAO

Testing & Development Centre, Electronics Hyderabad

SHRI M. N. SOMASUNDARAM

Air India, New Delhi

SHRI A. I. HYDER ( Alternate )

Shri S. P. Sachdev, Director (Elec tech)

Director General, ISI ( Ex-officio Member )

Secretaries

SHRI H. C. DUNEJA Assistant Director (Elec tech), ISI

SHRI R. S. SARMA Assistant Director (Elec tech), ISI

# Indian Standard

# DIMENSIONS FOR GENERAL PURPOSE PUSH-PULL SINGLE-POLE CIRCUIT-BREAKERS FOR AIRCRAFT

### 0. FOREWORD

- **0.1** This standard was adopted by the Indian Standards Institution on 25 July 1978, after the draft finalized by the Aircraft Electrical Equipment Sectional Committee had been approved by the Electrotechnical Division Council.
- **0.2** This standard is based on ISO 530-1975(E) 'Aircraft—General purpose push-pull single-pole circuit-breakers—Dimensions', issued by the International Organization for Standardization.
- 0.3 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value, observed or calculated, expressing the result of a test, shall be rounded off in accordance with IS:2-1960\*. The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.

#### 1. SCOPE


1.1 This standard specifies the dimensions for general purpose push-pull single-pole circuit-breakers for aircraft.

#### 2. DIMENSIONS

- 2.1 The dimensions of general purpose push-pull single-pole aircraft circuit-breakers, of ratings up to and including 35A, shall not exceed those shown in Fig. 1.
- 2.2 The circuit-breaker shall have at the centre of the front face of the case a 12 mm diameter, 1 mm pitch male thread for fixing through the mounting panel.
- 2.3 The holes in the mounting panel for fixing the circuit-breaker shall be as shown in Fig. 2. The small panel hole may be used to prevent rotation of the circuit-breaker.

<sup>\*</sup>Rules for rounding off numerical values (revised).

### IS: 8852 - 1978



Dimension	Dimension			
<i>A</i> †	63 Max	F	9 <i>Max</i>	
$\boldsymbol{\mathit{B}}$	19·5 Max	$\boldsymbol{G}$	16·3 Max	
$\boldsymbol{C}$	33 <i>Max</i>	H	22.8 Max	
D	10·4 Max	J*	80	
$\boldsymbol{E}$	8·4 Max			

All dimensions in millimetres.

Fig. 1 Dimensions of Single-Pole Circuit-Breakers ( Of Ratings up to and Including 35A )




Fig. 2 Panel Drilling

<sup>\*</sup>Recommended minimum clearance. †Including terminations.